MERIDIAN
FLOORING PRODUCTS

Meridian Flooring ProductsMultclic12 Click

Size:	6” x 48” (150 mm x 1220 mm)
Overall thickness:	3.2 mm
Wear layer:	0.30 mm (12 mil)
Urethane Coated:	Yes
Usage:	Residential, Commercial, Indoor
Warranty:	15 year Residential 5 year Light Commercial

Patterns:

MCLIC12-267	Brighton Oak
MCLIC12-900	Aurora Oak
MCLIC12-909	Pueblo Hickory
MCLIC12-950	Aspen Oak
MCLIC12-951	Castle Rock
MCLIC12-952	Arvada Oak
MCLIC12-953	Almosa
MCLIC12-954	Duran Hickory

Meridian Flooring Products Multiflor6 Plank

Size:	6” x 48” (152.4 mm x 1219.2 mm)
Overall thickness:	2 mm
Wear layer:	0.15 mm (6 mil)
Urethane Coated:	Yes
Usage:	Residential, Commercial, Indoor
Warranty:	15 year Residential 5 year Light Commercial

Patterns:

MFLOR6-267	Brighton Oak
MFLOR6-900	Aurora Oak
MFLOR6-909	Pueblo Hickory
MFLOR6-950	Aspen Oak
MFLOR6-951	Castle Rock
MFLOR6-952	Arvada Oak
MFLOR6-953	Almosa
MFLOR6-954	Duran Hickory

P.O. Box 1083
2732 Highway 74 West
Wadesboro, NC 28170
jkronemeyer@meridianfloor.com
Telephone:
Canada: (905) 394-1724
US: (704) 690-3555

MERIDIAN
FLOORING PRODUCTS

Test	Test Result	Requirements/Tolerance
Size and Tolerance ASTM F 2055	Passes	As specified 0.016 in/ lin.ft.
Thickness ASTM F F 386	Passes	As specified .005 in/ lin.ft
Squareness ASTM F 2055	Passes	Max .010 in
ASTM F970-07 (2011) Residual Indentation	Passes	0.03 mm
Slip Resistance ASTM C1028	Exceeds	Exceeds ADA and OSHA Recommendations
Flammability ASTM D2859-06/CPSC FF1-70	Passes	
Smoke Density ASTM E662-06	Passes	< 450
Critical Radiant Flux ASTM E648-06	Passes	Class 1
Slip Resistance ASTM 1028	Pass/Safe	ADA Compliant
Static Load Limit ASTM F 970	Pass	1,000 psi

P.O. Box 1083
2732 Highway 74 West
Wadesboro, NC 28170
jkronemeyer@meridianfloor.com
Telephone:
Canada: (905) 394-1724
US: (704) 690-3555