

Natchez 5.2mm | SPC

Technical Data Sheet

General Specifications

Overall Thickness: 5.2 mm

Wear Layer Thickness: 0.5 mm (20 mil)
Underlayment Thickness & Type: 1.0mm XPO Foam

Product Type: Drop Lock Rigid Core

Core Type: Solid Polymeric Core (SPC)

Dimensions: 5.75" x 47.75"

Finish: High Performance Urethane

Surface: Embossed w/ Microbevel

Residential Warranty: Lifetime Light Commercial Warranty: 15 Years

Carton Quantity: 10 Pieces (19.067 sq. ft.)

Carton Weight: 32 lbs. Cartons / Pallet: 54

Technical Specifications

ASTM F3261 - Rigid Core Specification: Class I, Type B, Grade 1, Backing Class B

ISO 24337 - Size & Squareness: Passes, \pm 1.5 mm size, \pm 0.25 mm squareness

ASTM F387 - Thickness of Flooring w/ Foam Layer: Passes, ± 0.2 mm

ASTM F410 - Wear Layer Thickness: Passes, $\geq 0.5 \text{ mm}$

ISO 24337 - Flatness: Passes, \pm 0.2 mm width, < 0.2% length

ISO 24337 - Joint Opening: Passes, \leq 0.2 mm ISO 24337 - Joint Ledging: Passes, \leq 0.15 mm ASTM F1914 - Residual Indentation: Passes, \leq 0.18 mm Passes, \leq 0.18 mm

ISO 23999 - Dimensional Stability: Passes, $\leq 0.2\%$ / lin. ft.

ISO 23999 - Curl: Passes, ≤ 2 mm

ASTM F925 - Chemical Resistance: Passes ASTM F3621 requirements

ASTM F1514 - Resistance to Heat: Passes, $< \Delta E \ 8$ ASTM F1515 - Resistance to Light: Passes, $< \Delta E \ 8$

ASTM F970 - Static Load: Passes, \leq 0.13 mm indent, 250 lbs.

ASTM E648 (NFPA 253) - Critical Radiant Flux: Class 1, > 0.45 W/cm2

ASTM E662 (NFPA 258) - Smoke Density: Passes, < 450

ASTM D2047 / UL 410 - Slip Resistance: > 0.5 SCOF (no ramps)

ASTM E492 / E989 - Impact Insulation Class: IIC 57^* , 55^* , 67^{\S} ASTM E90 / E413 - Sound Transmission Class: STC 50^* , 60^{\S} , 61^{\S}

ASTM E2179 - Delta Impact Insulation Class: \triangle IIC 25*

* 6" concrete | * 18" OWT | § 6" concrete, gypsum ceiling

Disclaimer: These test results were independently tested, using material from standard production, in accordance with product-specific standard test methods. Physical and performance testing may vary, within tolerances, depending on the testing apparatus and/or production lot used. Be sure to use the most recently published versions of all reference documents, specifications and test methods. To purchase the most recent version of the above mentioned ASTM and ISO standards, please visit www.astm.org. or www.iso.org, respectively. Test reports are available upon request.