



REVERB

NOISE CONTROL UNDERLAYMENT

APPLICATION

- RESIDENTIAL
- COMMERCIAL

APPROVED FOR USE UNDER

- LUXURY VINYL TILES AND PLANKS (2MM AND UP)
- LAMINATE
- ENGINEERED WOOD
- HARDWOOD
- SPC (WITH/WITHOUT ATTACHED BACKING)
- WPC (WITH/WITHOUT ATTACHED BACKING)
- CARPET TILE

DIMENSIONS AND PACKAGING

- ROLL SIZE **200/SF**
- ROLL WIDTH **36"**
- ROLL WEIGHT **22 LBS**
- ROLLS/PALLET **30**
- PALLETS/TRUCK **52 DOUBLE STACKED**
- MATERIAL **RUBBER W/ RECYCLED**
- COMPOSITION **TIRE CRUMB**
- THICKNESS **1.5 MM**
- DENSITY **30LB/FT³**

SPECIFICATIONS +/- 15%

- MOISTURE BARRIER
- COMPRESSION SET
- INDENTATION
- SMOKE DENSITY
- FLAMMABILITY TEST
- THERMAL RESISTANCE (R-VALUE)
- ANTIMICROBIAL PROTECTION
- INDOOR AIR QUALITY
- INSTALLATION METHODS
- WARRANTY

OPTIONAL

(INCLUDES LIP & TAPE SYSTEM)

- **ASTM D 1055-97** (22H, 70C)- 16%
- **ASTM F1914 - 12%**
- **ASTM A662**- LESS THAN 89 MAX
- **ASTM D 2859** (DOC FF 1-70) - PASS

0.205

YES

CRI CERTIFIED FOR LOW EMITTING MATERIALS

FLOAT, DOUBLE GLUE, NAIL DOWN, STAPLE

LIMITED LIFETIME

APPROVED SUBSTRATES

- COMPLETELY CURED CONCRETE
- INTERIOR PLYWOOD
- CEMENT BACKER UNITS
- OSB (SKIM COAT MAY BE REQUIRED)
- GYPCRETE

SOUND RATINGS OVER 6" SLAB

- LUXURY VINYL TILES & PLANKS **DELTA 25DB
IIC 69, STC 63**
- LAMINATE & WOOD PRODUCTS **DELTA 22DB
IIC 68, STC 63**

SUSTAINABILITY AND LEED®

- CONTENT **100% VIRGIN RUBBER WITH RECYCLED TIRE CRUMB**
- RECYCLABILITY **100% POST CONSUMER**
- CERTIFICATION **GREEN LABEL PLUS**
- LEED® Credit EQ 4.3 **LOW-EMITTING MATERIALS**
- LEED® Credit MRc5.1,5.2 **REGIONAL CONTENT 20-30%**
- LEED® Credit IEQp3 **MINIMUM ACOUSTICAL PERFORMANCE**
- LEED® MRC4 **RECYCLED CONTENT 10-20%**